[X] Industrial [X] Professional [_] Consumers



1.2

MARNEUCE- Marine Varnish

Code: 10120000



Version: 9 Revision: 28/01/2020 Previous revision: 22/01/2019 Date of printing: 28/01/2020

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER: MARNEUCE- Marine Varnish Code: 10120000

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended uses (main technical functions):

Trim varnish for wood, solvent-borne.

Sectors of use:

Industrial manufacturing (SU3).

Professional uses (SU22).

Uses advised against:

This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as

'Intended or identified uses'.

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

Not restricted.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

NEUCE - Indústria de Tintas, S.A.

Rua Francisco Rocha - Aptdo . 4514 - 3700-892 - Romariz SJM (Portugal) Phone: +351 256 840040 - Fax: +351 256 840049

E-mail address of the person responsible for the Safety Data Sheet:

e-mail: geral@neuce.pt

1.4 EMERGENCY TELEPHONE NUMBER: +351 256 840041 (9:00-18:30 h.) (working hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

Classification in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP).

DANGER: Flam. Liq. 3:H226 | Skin Irrit. 2:H315 | STOT SE (rarcos is) 3:H336 | STOT RE 1:H372i | Aquatic Chronic 2:H411 | EUH066

Danger class Cla	assification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Sk ST ST Ac	kin Irrit. 2:H315 c) TOT SE (nar cos is) 3: H336 c) TOT RE 1:H372 c)	Cat.3 Cat.2 Cat.3 Cat.1 Cat.2	- Skin Inhalation Inhalation - Skin	- Skin CNS Systemic - Skin	- Irritation Narcosis Damage - Dryness, Cracking

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2 LABEL ELEMENTS:

P280F



This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP)

H226 Flammable liquid and vapour.

H372i Causes damage to organs through prolonged or repeated exposure if inhaled.

H315 Causes skin irritation. H336

May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements: P102

P303+P361+P353-P352-P312

Keep out of reach of children. P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash with

plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell.



Code: 10120000



IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if P304+P340-P312

vou feel unwell.

P273-P391-P501a Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local

regulations.

Supplementary statements:

EUH 208 Contains bis(hydroxyphenylbenzotriazole) derivative, 2-butanone-oxime, hydroxyphenylbenzotriazole derivative,

bis(12266-pentamethyl-4-piperydynyl) sebacate. May produce an allergic reaction.

Substances that contribute to classification: Hydrocarbons C9-C12 (aromatics 2-25%)

Naphtha (petroleum), hydrodesulfurized heavy

2.3 OTHER HAZARDS

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

Other physicochemical hazards: # No other relevant adverse effects are known.
Other adverse human health effects: # No other relevant adverse effects are known.

Other negative environmental effects: # Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCES 3.1

Not applicable (mixture).

3.2 MIXTURES:

This product is a mixture.

Chemical description

Solution of long-oil alkyd resin.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

25 < 30 % Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

(1) (1) (1)

(CAS: 64742-82-1), List No. 919-446-0 REACH: 01-2119458049-33 CLP: Danger: Flam. Lig. 3:H226 | STOT SE (narcosis) 3:H336 | STOT RE 1:H372i | Asp. Tox. 1:H304 | Aquatic Chronic 2:H411 | EUH066

Autoclassified < REACH

20 < 25 % Naphtha (petroleum), hydrodesulfurized heavy

CAS: 64742-82-1, EC: 265-185-4 CLP: Danger: Flam. Liq. 3:H226 | Skin Irrit. 2:H315 | STOT SE (rar cos is) 3:H336 |

Index No. 649-330-00-2 (Note H,P) < ATP01

Asp. Tox. 1:H304 | Aquatic Chronic 2:H411

Bis(hydroxyphenylbenzotriazole) derivative CAS: 104810-48-2, List No. 600-603-4 0,1 < 0,3 %

⟨!⟩⟨₺⟩

CLP: Warning: Skin Sens. 1:H317 | Aquatic Chronic 2:H411

Autoclassified

2-butanone-oxime CAS: 96-29-7, EC: 202-496-6 < 0,25 %

⟨₹**⟩**⟨**\$**⟩⟨!⟩

CLP: Danger: Acute Tox. (skin) 4:H312 | Eye Dam. 1:H318 | Skin Sens. 1:H317 | Carc.

Index No. 616-014-00-0

< CLP00

< 0,25 % Hydroxyphenylbenzotriazole derivative

CÁS: 104810-47-1, EC: 400-830-7 **(!)**

CLP: Warning: Skin Sens. 1:H317 | Aquatic Chronic 2:H411

Index No. 607-176-00-3 < CLP00

< 0,20 %

Bis(12266-pentamethyl-4-piperydynyl) sebacate

<!>⟨₺⟩

CAS: 41556-26-7, EC: 255-437-1

CLP: Warning: Skin Sens. 1:H317 | Aquatic Acute 1:H400 (M=1) | Aquatic Chronic

1:H410 (M=1)

< 0,20 %

Cobalt bis(2-ethylhexanoate)

♦♦(!)**﴿**

CAS: 136-52-7, EC: 205-250-6 CLP: Warning: Acute Tox. (oral) 4:H302 | Eye Irrit. 2:H319 | Skin Sens. 1:H317 | Repr. 2:H361f | Aquatic Acute 1:H400 (M=1) | Aquatic Chronic 3:H412

Autoclassified

Autoclassified

< REACH

Impurities:

Content of benzene < 0.1%.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 15/01/2019.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.



SECTION 4: FIRST AID MEASURES

4.1 <u>DESCRIPTION OF FIRST-AID MEASURES:</u>



In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation:	# Vapours may cause drowsiness and dizziness.	# Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin:	# Skin contact causes redness.	# Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
<u>Eyes:</u>	# Contact with the eyes may produce slight redness.	# Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
Ingestion:	# If swallowed, may cause irritation of the mouth, throat and oesophagus.	# If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
Notes to physician: # Treatment should be directed at the control of symptoms and the clinical condition of the patient.
Antidotes and contraindications: # Specific antidote not known.

SECTION 5: FIRE-FIGHTING MEASURES

- 5.1 <u>EXTINGUISHING MEDIA:</u>
 - # Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist.
- 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: # Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: # Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
 - # Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product.
- 6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

- 6.3 <u>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</u>
 - # Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.
- 6.4 <u>REFERENCE TO OTHER SECTIONS:</u>

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.



Code: 10120000



Revision: 28/01/2020

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: 7.1

Comply with the existing legislation on health and safety at work.

Avoid any type of leakage or escape. Keep the container tightly closed.

Recommendations for the prevention of fire and explosion ris

Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.

43*

245*

0.6* - 7.1

°C

% Volume 25°C

Flash point Autoignition temperature

Upper/lower flammability or explosive limits
Recommendations for the prevention of toxicological risks:

Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

Recommendations for the prevention of environmental contamination:

Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.

According to current legislation. Class of storage

Maximum storage period # 24. months

Temperature interval # min: 5. °C, max: 35. °C (recommended).

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.

According to current legislation.

Limit quantity (Seveso III): # Directive 2012/18/EU:

- Named dangerous substances/mixtures: None
- Hazard categories and lower-/upperthreshold quantities in tonnes (t):
- Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t).
- Health hazards: Not applicable
- Environmental hazards: Toxic to aquatic life with long lasting effects (E2) (200t/500t).
- Other hazards: Not applicable.
- Threshold quantity for the application of lower-tier requirements: 200 tons
- Threshold quantity for the application of upper-tier requirements: 500 tons

The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.



Code: 10120000



SPECIFIC END USES: 7.3

For the use of this product do not exist particular recommendations apart from that already indicated.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **CONTROL PARAMETERS:**

*# If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2018	<u>Year</u>	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Hydrocarbons C9-C12 (aromatics 2-25%)		100.	-	-	-	
Naphtha (petroleum), hydrodesulfurized heavy		100.	525.	-	-	Recommended
Bis(hydroxyphenylbenzotriazole) derivative		-	1.0	-	-	Internal value
Hydroxyphenylbenzotriazole derivative		-	1.0	-	-	Recommended
Bis(12266-pentamethyl-4-piperydynyl) sebacate		-	1.0	-	-	Internal value

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

BIOLOGICAL LIMIT VALUES:

Not available

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recomme reded by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers: - Systemic effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%)	DNEL Inhalation mg/m3 570. (a)	330. (c)	DNEL Cutaneous mg/kg bw/d s/r (a)	21.0 (c)	DNEL Oral mg/kg bw/d - (a)	- (c)
Derived no-effect level, workers: - Local effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%)	DNEL Inhalation mg/m3 s/r (a)	s/r (c)	DNEL Cutaneous mg/cm2 s/r (a)	s/r (c)	DNEL Eyes mg/cm2 s/r (a)	- (c)

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

- (a) Acute, short-term exposure, (c) Chronic, long-term or repeated exposure.
- (-) DNEL not available (without data of registration REACH).
- s/r DNEL not derived (not identified hazard).





Revision: 28/01/2020

PREDICTED NO-EFFECT CONCENTRATION (PNEC):

PREDICTED NO-BITECT CONCENTRATION (FINE).					
Predicted no-effect concentration, aquatic organisms: - Fresh water, marine water and intermittent release: Hydrocarbons C9-C12 (aromatics 2-25%)	PNEC Fresh water mg/l uvcb	PNEC Marine mg/l uvcb	PNEC Intermittent mg/l uvcb		
- Wastewater treatment plants (STP) and sediments in fresh- and marine water: Hydrocarbons C9-C12 (aromatics 2-25%)	PNEC STP mg/l uvcb	PNEC Sediments mg/kg dw/d uvcb	PNEC Sediments mg/kg dw/d uvcb		
Predicted no-effect concentration, terrestrial organisms: - Air, soil and effects for predators and humans: Hydrocarbons C9-C12 (aromatics 2-25%)	PNEC Air mg/m3 uvcb	PNEC Soil mg/kg dw/d uvcb	PNEC Oral mg/kg dw/d uvcb		

uvcb - The substance has an unknown or variable composition (UVCB). The conventional methods to derive the PNEC are not appropriate and it is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.

8.2

MARNEUCE- Marine Varnish

Code: 10120000



Revision: 28/01/2020

EXPOSURE CONTROLS:

ENGINEERING MEASURES:











Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

<u>Protection of respiratory system:</u> # Avoid the inhalation of product.

Protection of eyes and face: # It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: # It is recommended to install emergency showers close to the working area.

OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:
As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning maint enance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc...), you should consult the informative brochures provided by the manufacturers of PPE.

Trialiaractar cro of 11 Er	
Mask:	# Mask for gases and vapours (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers.
Safety goggles:	# Safety goggles with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	# No.
Gloves:	# Gloves resistant against chemicals (EN374).
Boots:	# No.
Apron:	# No.
Clothing:	# Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment.

Spills on the soil: # Prevent contamination of soil.

Spills in water: # Do not allow to escape into drains, sewers or water courses.
- Water Management Act: # This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

Emissions to the atmosphere: # Not applicable.

Code: 10120000



Relative water

Relative

Revision: 28/01/2020

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	INFORMATIONON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

- Physical state Colour
- Odour
- Odour threshold

pH-value - nH

Change of state
- Melting point

- Initial boiling point
- Density
- Vapour density
- Relative density

Stability

Decomposition temperature

- <u>Viscosity:</u>
 Dynamic viscosity
- Kinematic viscosity
- Viscosity (flow time)

- Volatility: ^ Evaporation rate
- Vapour pressure
- Vapour pressure

Solubility(ies)

- Solubility in water
- Liposolubility
- Partition coefficient: n-octanol/water

Flammability:

- Flash point
- Upper/lower flammability or explosive limits
- Autoignition temperature

Explosive properties:

Not available.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

OTHER INFORMATION: 9.2

Heat of combustion

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7

Liauid. Colourless.

Characteristic

Not available

Not applicable

Not available (mixture).

Not applicable (mixture).

 0.9 ± 0.05

85. ± 13.

Not applicable (non-aqueous media).

150*

278.

100.

151*

*12.7**

5.6*

Not available (mixture untested).

Not applicable (mixture).

0.6* - 7.1

9027*

48.5

°C at 760 mmHg

20°C

at 20/4°C

Not available (technical impossibility to obtain the data).

mm2/s at 40°C

sec.FC4 20°C

nBuAc=100 25°C

% Volume 25°C

Kcal/kg

% Weight

mmHg at 20°C kPa at 50°C

cps

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY:

Corrosivity to metals: # It is not corrosive to metals.

Pyrophorical properties: # It is not pyrophoric.

CHEMICAL STABILITY: 10.2

- # Stable under recommended storage and handling conditions.
- 10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with oxidizing agents, acids.

10.4 CONDITIONS TO AVOID:

Heat: # Keep away from sources of heat.

Light: # If possible, avoid direct contact with sunlight.

Air: # The product is not affected by exposure to air, but should not be left the containers open.

Humidity: # Avoid extreme humidity conditions.

Pressure: # Not relevant.
Shock: # The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

10.5 **INCOMPATIBLE MATERIALS:**

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.

Revision: 28/01/2020

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxic dog call dassification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. $1272/2008 \sim 2018/1480$ (CLP).

11.1 INFORMATIONON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients: Hydrocarbons C9-C12 (aromatics 2-25%) Naphtha (petroleum), hydrodesulfurized heavy Bis (hydroxyphenylbenzotriazole) derivative 2-butanone-oxime Hydroxyphenylbenzotriazole derivative Bis (12266-pentamethyl-4-piperydynyl) sebacate Cobalt bis (2-ethylhexanoate)	LD50 (OECD 401) mg/kg bw oral > 5000. Rat 6000. Rat 2400. Rat 2400. Rat > 2000. Rat > 2000. Rat 1600. Rat	LD50 (OFCD 402) mg/kg bw cutaneous > 2000. Rabbit 3000. Rat 1840. Rabbit > 2000. Rat	LC50 (OECD 403) mg/m3-4h inhalation > 13100. Rat > 7630. Rat > 4830. Rat > 5800. Rat
Estimates of acute toxicity (ATE) for individual ingredients: 2-butanone-oxime Cobalt bis(2-ethylhexanoate)	ATE mg/kg bw oral - 1600.	ATE mg/kg bw cutaneous 1840.	ATE mg/m3-4h inhalation - -

- (*) Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

 (-) The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level 2-butanone-oxime	NOAEL Oral mg/kg bw/d 125. Rat	NOAEL Cutaneous mg/kg bw/d	NOAEC Inhalation mg/m3 90. Rat
Lowest observed adverse effect level	LOAEL Oral mg/kg bw/d	LOAEL Cutaneous mg/kg bw/d	LOAEC Inhalation
2-butanone-oxime	40. Rat	1119,19 211, 2	1113,1112

INFORMATIONON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m3	-	# Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/QP 3.1.3.6.
Skin: Not classified	ATE > 2000 mg/kg bw	-	# Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/QLP 3.1.3.6.
Eyes: Not classified	Not available	-	# Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 2000 mg/kg bw	-	# Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

Code: 10120000



Revision: 28/01/2020

LUKKUSIUN	/ IKKI IA HUJIV /	SENSITISATION:

CORROSION/IRRIATION/SENSITISATION:						
Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria		
Respirat any corros ion/inritation Not classified	-	-	# Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.		
Skin corrosion/irritation:	Skin	Cat.2	# IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.		
Serious eye damage/irritation: Not classified	-	-	# Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.		
Respiratory sensitisation: Not classified	-	-	# Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.		
Skin sensitisation: Not classified	-	-	# Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/QP 3.4.3.3.		

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Aspiration hazard: Not classified	-	-	# Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

| SPECIFIC TARGET OR GANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Systemic:	RE	Systemic	Cat.1	# TOXIC: Causes damage to organs through prolonged or repeated exposure if inhaled.	GHS/CLP 3.8.3.4.
Cutaneous:	RE	Skin	-	# DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
Neurological:	SE	CNS	Cat.3	# NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

Carcinogenic effects: # It is not considered as a carcinogenic product.

Genotoxicity: # It is not considered as a mutagenic product.

Toxicity for reproduction: # Does not harm fertility. Does not harm the unborn child.

Effects via lactation: # Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: # Not available.

Short-term exposure: # May irritate the eyes and skin. Irritating to skin. Long-term or repeated exposure: # Not available.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption: # Not available.

Basic toxicokinetics: # Not available.

ADDITIONAL INFORMATION:

Not available.

Code: 10120000



Revision: 28/01/2020

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008 \sim 2018/1480 (CLP).

171	TOXICITY:
12.1	I IU XIU II II:

Acute toxicity in aquatic environment for individual ingredients: Hydrocarbons C9-C12 (aromatics 2-25%) Naphtha (petroleum), hydrodesulfurized heavy Bis (hydroxyphenylbenzotriazole) derivative 2-butanone-oxime Hydroxyphenylbenzotriazole derivative Bis (12266-pentamethyl-4-piperydynyl) sebacate Cobalt bis (2-ethylhexanoate)	LC50 (OECD 203) mg/l-96hours > 10. Fishes > 2.6 Fishes > 2.8 Fishes 843. Fishes > 2.8 Fishes 0.97 Fishes > 1.5 Fishes	EC50 (OECD 202) mg/I48hours > 10. Daphnia > 2.3 Daphnia > 3.8 Daphnia 750. Daphnia > 3.8 Daphnia > 20. Daphnia 0.61 Daphnia	EC50 (OECD 201) mg/l-72hours > 4.6 Algae > 10. Algae > 9.0 Algae > 83. Algae > 9.0 Algae O.20 Algae
Cobait bis(2-et lyllexalibate)	> 1.3 FISHES	0.01 Dapilila	0.20 Algae
No observed effect concentration	NOEC (OECD 210)	NOEC (OECD 211)	NOEC (OECD 201) mg/l-72hours
2-butanone-oxime	50. Fishes	> 100. Daphnia	

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
Acute aquatic toxicity: Not classified	-	# Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
Chronic aquatic toxicity:	Cat.2	# TOXIC: Toxic to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components. CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

<u>Aerobic biodegradation</u>	<u>DQO</u>	%DBO/[Biodegradability
for individual ingredients:	mgO2/g	5 days 14	days 28 (days	
Hydrocarbons C9-C12 (aromatics 2-25%)					Easy
Naphtha (petroleum), hydrodesulfurized heavy		24.	52.	74.	Easy
Bis(hydroxyphenylbenzotriazole) derivative					Not available
2-butanone-oxime					Inherently
Hydroxyphenylbenzotriazole derivative	1840.			~ 12.	Not easy
Bis(12266-pentamethyl-4-piperydynyl) sebacate					Not easy
Cobalt bis (2-ethylhexanoate)					Not easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

	Bioaccumulation	log Pow	<u>BCF</u>		<u>Potential</u>
	for individual ingredients:	F.65	L/kg	(- \)	Niet er eilelele
	Hydrocarbons C9-C12 (aromatics 2-25%)	5.65	> 100.	(calculated)	Not available
	Naphtha (petroleum), hydrodesulfurized heavy	5.65	> 100.	(calculated)	Not available
	Bis (hydroxyphenyl benzotriazole) derivative				Not available
	2-butanone-oxime	0.590	3.2	(calculated)	Not available
	Hydroxyphenylbenzotriazole derivative				Not available
	Bis(12266-pentamethyl-4-piperydynyl) sebacate	2.37			Not available
	Cobalt bis (2-ethylhexanoate)	2.96	24.	(calculated)	Not available
_					

12.4 MOBILITY IN SOIL:

Not available.

Mobility for individual ingredients :	log Koc	Constant of Henry Pa·m3/mol 20°C	<u>Potential</u>
Hydrocarbons C9-C12 (aromatics 2-25%)	4.90	12 112, 112 2	Not available
Naphtha (petroleum), hydrodesulfurized heavy	4.90		Not available
Bis(hydroxyphenylbenzotriazole) derivative			Not available
2-butanone-oxime	0.550		Not available
Hydroxyphenylbenzotriazole derivative			Not available
Bis(12266-pentamethyl-4-piperydynyl) sebacate	1.98		Not available
Cobalt bis(2-ethylhexanoate)	3.05		Not available



Code: 10120000



RESULTS OF PBT AND VPVB ASSESMENT: 12.5 Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfil the PBT/vPvB criteria.

OTHER ADVERSE EFFECTS: 12.6

Ozone depletion potential: # Not available.

Photochemical ozone creation potential: # Not available.

Earth global warming potential: # In case of fire or incineration liberates CO2.

Endocrine disrupting potential: # Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS: # Directive 2008/98/EC~Regulation (EU) no. 1357/2014: 13.1

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: # Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1	LIN NI IMBER: 1263	

14.2 JN PROPER SHIPPING NAME:

TRANSPORT HAZARD CLASS(ES): 14.3

Transport by road (ADR 2019) and Transport by rail (RID 2019):

Class: III - Packing group: Classification code:

Tunnel restriction code: (D/E) 3, max. ADR 1.1.3.6. 1000 L Transport category: Limited quantities: 5 L (see total exemptions ADR 3.4) Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4

Yes.

Transport by sea (IMDG 38-16):

- Class: Packing group: IIIEmergency Sheet (EmS): F-E,S E First Aid Guide (MFAG): 310,313

Marine pollutant:

- Transport document: Shipping Bill of lading.

Transport by air (ICAO/IATA 2018):

Packing group: III

- Transport document: Air Bill of lading.

Transport by inland waterways (ADN):

Not available.

14.4 PACKING GROUP:

14.6

See section 14.3

14.5 **ENVIRONMENTAL HAZARDS**

Classified as hazardous for the environment.

SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX LIOF MARPOL 73/78 AND THE IBC CODE # Not applicable.

SECTION 15: REGULATORY INFORMATION

<u>EU SAFETY, HEALTH AND EN VIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:</u> 15.1

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

<u>Tactile warning of danger:</u> Not applicable (product for professional or industrial use).













Code: 10120000



Revision: 28/01/2020

<u>Child safety protection:</u> Not applicable (product for professional or industrial use).

VOC information on the label:

Contains VOC max. 400. g/l - The limit value 2004/42/CE-IIA cat. e) for the product ready for use is VOC max. 400. g/l (2010).

OTHER REGULATIONS:

Responsabilidade ambiental:

A utilização deste produto em Portugal fica sujeita ao regime de responsabilidade ambiental previsto no DL.147/2008.

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: OTHER INFORMATION

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2018/1480 (CLP), Annex III:

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H351 Suspected of causing cancer. H361f Suspected of damage fertility. H372i Causes damage to organs through prolonged or repeated exposure if inhaled.

Notes related to the identification, classification and labelling of the substances:

Note H: The classification and label shown for this substance applies to the dangerous property(ies) indicated by the risk phrase(s) in combination with the category(ies) of danger shown.

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1% w/w benzene (EC No. 200-753-7).

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- # · European Chemicals Agency: ECHA, http://echa.europa.eu/
- # · Access to European Union Law, http://eur-lex.europa.eu/
- · Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- · Threshold Limit Values, (AGCIH, 2017).
- European agreement on the international carriage of dangerous goods by road, (ADR 2019)
- · International Maritime Dangerous Goods Code IMDG including Amendment 38-16 (IMO, 2016).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- # · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- # GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- # · CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- # · EINECS: European Inventory of Existing Commercial Chemical Substances.
- # · ELINCS: European List of Notified Chemical Substances.
- # · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- # · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- * · SVHC: Substances of Very High Concern.
- # · PBT: Persistent, bioaccumulable and toxic substances.
- # · vPvB: Very persistent and very bioaccumulable substances.
- # · VPVB. Very persistent and very broaccuin # · DNEL: Derived No-Effect Level (REACH).
- # · PNEC: Predicted No-Effect Concentration (REACH).
- # · LD50: Lethal dose, 50 percent.
- # · LC50: Lethal concentration, 50 percent.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

 HISTORIC:
 Revision:

 Version: 8
 22/01/2019

 Version: 9
 28/01/2020

Changes since previous Safety Data Sheet:

* Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.