

1.1

1.4

RH10 WATERPROOFER



Revision: 22/05/2020

[X] Industrial [X] Professional [] Consumers

Version 10 Revision: 22/05/2020 Previous revision: 03/02/2015 Date of printing: 22/05/2020

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT IDENTFIER: RH10 WATERPROOFER Code: 22 08

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended uses (main technical functions):

Hydrophobic primer, solven t-borne.

- # Industrial manufacturing (SU3).
- # Professional uses (SU22).

Uses advised against:

This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'htended or identified uses'. Restrictions on manufacture, placing on market and use, according to Arnex XMI of Regulation (EC)No. 1907/2006:

Not restricted

DETALS OF THE SUPPLIER OF THE SAFETY DATASHEET: 1.3

NEUCE - Indústria de Tintas, S. A

Rua Francisco Rocha - Apt.do. 4514 - 3700-892 - Romariz SJM (Pottugal)

Phone: +351 256 840040 - Fax: +351 256 840049

E-mail address of the person responsible for the Safety Data Sheet:

e-mail: geral@neuce.pt

EMERGENCY TELEPHONE NUMBER +351 256 840041 (9:00-18:30 h.) (working hours)

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE 2.1

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly dassified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

ance with Regulation (EU) No. 1272/2008~2018/1480 (CLP):

WARNING: Flam. Liq. 3:H226 | Skin Irrit. 2:H315 | STOT SE (narcosis) 3:H336 | Aquatic Chronic 2:H411 | EUH066

Danger dass	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Physicochemical: thuman health: thuman health: Environment:	Flam. Liq. 3:H226 a) Skin Irit. 2:H315 c) STOTSE (narcosis) 3:H336 c) Aquatic Chronic 2:H411 c) EUH066 c)	Cat.3 Cat.2 Cat.3 Cat.2	- Skin Inhalation - Skin	- Skin CNS - Skin	Irritation Narcosis - Dryness, Cracking

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

LABEL ELEMENTS 2.2



This product is labelled with the signal word WARNING in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP)

Hazard statements

H226 H315

H336 H411 May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Flammable liquid and vapour.

Causes skin irritation.

ecautionary statements:

P102 P210

P304+P340-P312

P273-P391-P501a

P280F

P303+P361+P353-P352-P312

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection.

IF ON SKIN (or hair): Take off immediately all contaminated dothing. Rinse skin with water or shower. Wash with plenty of soap and

water. Calla POISO N CENTER or doctorifyou feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local regulations.

Code: 22.08



Revision: 22/05/2020

Supplementary statements:

None.

Substances that contribute to das

Naphtha (petroleum), hydrotreated heavy

2.3 OTHER HAZARDS

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: Other physicochemical hazards: # Vapours may form with air a mixture potentially flammable or explosive.

Other adverse human health effects: # No other relevant adverse effects are known.

Other negative environmental effects: # Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 SUBSTANCES:

Not applicable (mixture).

3.2 MIXTURES:

This product is a mixture.

Chemical description:

Solution of silicone resin.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

50 < 100 % Naphtha (petroleum), hydrotreated heavy

CAS: 64742-48-9, EC: 265-150-3

REACH: 01-2119486659-16

Index No. 649-327-00-6

CLP: Danger: Flam. Liq. 3:H226 | Skin Irrit. 2:H315 | STOT SE (n arcos is) 3 H336 | Asp. Tox. 1:H304 | Aquatic Chronic 2:H411 | EUH 066

(Note H,P)

< REACH

< 0,20 %

Dioctyltin dilaurate

CAS: 3648-18-8, EC: 222-883-3

CLP: Warning: STO TSE 2:H371o

Autodassified < REACH

◈

Content of benzene < 0.1%.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 16/01/2020.

Substances SVHC subject to authorisation, included in Amex XV of Regulation (EC) no. 1907/2006:

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None

RSISTENT, BIOACCUMULABLEAND TOXIC PBT, OR VER' STENT AND VERYBIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.





Revision: 22/05/2020

SECTION 4: FIRST AID MEASURES

4.1 **DESCRIPTION OF FIRST-ADMEASURES:**



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
hhalation:	# Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drow siness and, in extreme cases, unconsciousness.	# Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin:	# Skin contact causes redness. Prolonged contact may cause skin dryness.	# Remove immediately contaminated dothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin deanser. Do not use solvents or thinners.
<u>Eyes:</u>	# Contact with the eyes produces redness and pain.	# Remove contact lenses. Rinse eyes copiously by inigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the initation is reduced. Call a physician immediately.
Ingestion:	# If swallowed, may cause initation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	# If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2

The main symptoms and effects are indicated in sections 4.1 and 11.1

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: # Trea ment should be directed at the control of symptoms and the dirical condition of the patent.

Antidotes and contraindications: # Specific antidote not known.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 **EXTINGUISHING MEDIA:**

4.3

Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, formaldehyde. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: # Depending on magnitude of fire, heat-proof protective dothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: # Cool with water the tanks, astems or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENTAND EMERGENCY PROCEDURES: 6.1

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid die d contact with this pioduct Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

6.2 **ENVIRONMENTAL PRECAUTIONS:**

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.

REFERENCE TO OTHER SECTIONS: 6.4

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.



Code: 22.08



Revision: 22/05/2020

CLP 2.6.4.3.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Comply with the existing legislation on health and safety at work.

General recommendations

Avoid any type of leakage or escape. Keep the container tightly dosed.

Recommendations for the prevention of fire and explosion risk

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this mate italish ould only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used. 40. # ℃ 234* # ℃

234*

According to current legislation.

min: 5. °C, max: 35. °C (recommended).

24. months

- Flash point

Autoignition temperature

 Upper/lower flammability or explosive limits
 Recommendations for the prevention of toxicological risks: % Vdume 25℃ 0.6* - 7.1 # Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8. Recommendations for the prevention of environmental contamination:

Avoid any spillage in the environment. Pay special attention to the deaning water. In the case of acode nt a spillage, follow the instructions indicated in section 6.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES 7.2

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity con ditions. In order to avoid bakages, the containers, after use, should be dosed carefully and placed in a vertical position. For more information, see section 10.

Class of storage

Maximum storage period

Temperature interval

Incompatible materials:

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials. Type of packaging

According to current legislation.

Limit quantity (Seveso II): # Directive 2012/18/EU:

- Named dangerous substances/mixtures: None

- Hazard categories and lower-/upperthreshold quantities in tonnes (t):
- Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t).
- Health hazards: Not applicable
- Environmental hazards: Toxic to aquatic life with long lasting effects (E2) (200t/500t).
- Other hazards: Not applicable.
- Threshold quantity for the application of lower-tier requirements: 200 tons
- Threshold quantity for the application of upper-tier requirements: 500 tons
- Remarks:

The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Ann extlofthe Seveso Directive.

7.3

For the use of this product particular recommendations apart from that already indicated are not available.



Code: 22.08



Revision: 22/05/2020

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assesing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCH 2018	<u>Year</u>	TLVTWA		TLVSTEL		Remarks
Naphtha (petroleum), hydrotreated heavy Dioctytin dilaurate	1996	ppm 100.	mg/m3 525. 0.10	ppm	mg/m3 - 0.20	Recommended As Sn A3 , Skin

TLV-Threshold Limit Value, TWA-Time Weighted Average, STEL - Short Term Exposure Limit.

Skin - Danger of cutaneous absorption.

A3 - Carcinogenic in animals.

Dermal (Vd): # Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be or equal or greater importance even that inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

BIOLOGICAL LIMITVALUES:

Not available

DERMED NO-EFFECT LEVEL (DN EL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of heath, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers: - Systemic effects, acute and chronic: Naphtha (petroleum), hydrotreated heavy	DNEL hhalation mg/m3 - (a)	- (c)	DNEL Cutaneous mgkgbwld - (a)	- (c)	DNEL Oral mgkgbwld - (a)	- (c)
Derived no-effect level, workers: - Local effects, acute and chronic: Naphtha (petroleum), hydrotreated heavy	DNEL hhalation mg/m3 - (a)	- (c)	DNEL Cutaneous mg/cm2 - (a)	- (c)	DNEL Eyes mg/cm2 - (a)	- (c)

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(-) - DNEL not available (without data of registration REACH).

Revision: 22/05/2020



RH10 WATERPROOFER

Code: 22.08



PREDICTED NO-EFFECT CONCENTRATION (PNEC):

Predicted no-effect concentration, aquatic organisms: - Fresh water, marine water and intermittent release: Naphtha (petroleum), hydrotreated heavy	PNEC Fresh water mgl uvdb	PNEC Marine mgl uvcb	PNEC Intermittent mgl uvcb
- Wastewater treatment plants (STP) and sediments in fresh- and marine water. Naphtha (petroleum), hydrotreated heavy	PNEC STP	PNEC Sediments	PNEC Sediments
	mg/	mgkgdwld	mg/kgdwld
	uvdb	uvcb	uvcb
Predicted no-effect concentration, terrestrial organisms: - Air, soiland effects for predators and humans: Naphtha (petroleum), hydrotreated heavy	PNECAir	PNEC Soil	PNEC Oral
	mg/m3	mgkgdwld	mgkgdwld
	uvdb	uvcb	uvcb

uvcb - The substance has an unknown or variable composition (UVCB). The convertional methods to derive the PNEC are not appropriate and t is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.

8.2 EXPOSURE CONTROLS:

ENGINEERING MEASURES:











Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be wom.

Protection of respiratory system: # Avoid the inhalation of vapours.

Protection of eyes and face: # It is recommended to install water taps, sources or eyewash bottles with dean water close to the working area.

Protection of hands and skin: # It is recommended to install water taps or sources with dean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, deaning, maintenance, type and characteristics of the PPE, protection dass, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus. # Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular Safety goggles: intervals in accordance with the instructions of the manufacturer. Face shield: # No. Gloves: # Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted. Boots: # No. # No. Apron: Clothing: # Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENMRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: # Prevent contamination of soil.

Spills in water: # Do not allow to escape into drains, sewers or water courses.

Water Management Act: # This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

Emissions to the atmosphere: # Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.



Code: 22.08



Revision: 22/05/2020

Relative water

CLP 2.6.4.3.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES: Appearance Appearance Physical state

Colour

Odour

- Odour threshold

pH-value

Ha -

Change of state

- Melting point hitial boiling point

Density Vapour den sity

Relative density

Decomposition temperature

Viscosity:

Kinematic viscosity

Kinematic viscosity

Volatility:

- Evaporation rate

Va pour pressure Va pour pressure

Solubility(ies)

Solubility in water. Liposolubility

Partition coefficient: n-octanol/water

Flammability:

Flash point

Upper/lower flammability or explosive limits

Autoignition temperature

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

- VOC (supply)

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

Clear liquid.

Colourless.

Characteristic.

Not available

Not applicable

Limited

Not available (mixture).

Not applicable (mixture).

Not applicable (non-aqueous media).

0.8 ± 0.05 # at 20/4°C

1.5*

Not available (mixture untested).

Not applicable (mixture).

Not available (technical impossibility to obtain the data).

7.2 mm2/s at 40°C

26.4* nBuAc=100 25°C

1.5* kPa at 50℃

40. °C 0.6* - 7.1 % Vdume 25℃

8.3 # % Weight

726.0

mmHg at 20°C

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTMTY.

Corrosivity to metals: # It is not corrosive to metals.

Pyrophorical properties: # It is not pyrophoric.

10.2 CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

10.3 POSSBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with oxidizing agents, acids.

10.4 CONDITIONS TO AVOID:

Heat: # Keep away from sources of heat.

Light: # If possible, avoid direct contact with sunlight.

Air. # The product is not affected by exposure to air, but should not be left the containers open.

Humidity: # Avoid extreme humidity conditions.

Pressure: # Not relevant.

Shock: # The product is not senstive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and

breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

INCOMPATIBLE MATERIALS: 10.5

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.

HAZARDOUS DECOMPOSITION PRODUCTS: 10.6

As consequence of thermal decomposition, hazardous products may be produced: formaldehyde.



Code: 22.08



SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients: Naphtha (petroleum), hydrotreated heavy Dioctyltin dilaurate

LD50 (OECD 401) mg/kgbworal > 5000. Rat 6450. Rat

LD50 (OECD 402) mg/kgbwoutaneous > 2000. Rabbit

Rat

> 2000.

LC50 (OECD 403) mg/m3·4hinhalation > 7630. Rat

Estimates of acute toxicity (ATE)

for individual ingredients

Not classified as a product with acute toxicity.

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity.

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria		
Inhalation: Not dassified	ATE > 20000 mg/m3	-	# Not dassified as a product with acute toxicity if inhaled (based on available data, the dassification criteria are not met).	GHS/CLP 3.1.3.6.		
Skin: Not dassified	ATE > 2000 mg/kg bw	-	# Not dassified as a product with acute toxicity in contact with skin (based on available data, the dassification criteria are not met).	GHS/CLP 3.1.3.6.		
Eves: Not classified	Not available	-	# Not dassified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 12.5.		
hgestion: Not dassified	ATE > 2000 mg/kg bw	-	# Not dassified as a product with acute toxicity if swallowed (based on available data, the dassification criteria are not met).	GHS/OLP 3.1.3.6.		

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION:

Danger dass	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Respiratory corrosion/irritation: Not classified	-	-	# Not dassified as a product corrosive or imitant by inhalation (based on available data, the dassification criteria are not met).	GHS/CLP 126. 3834.
Skin corrosion/irritation:	Skin	Cat.2	# IRRITANT: Causes skin initation.	GHS/CLP 3233.
Serious eye damage/initation: Not dassified	-	-	# Not dassified as a product corrosive or initant in contact with eyes (based on available data, the dassification criteria are not met).	GHS/OLP 33333.
Respiratory sensitisation: Not classified	-	-	# Not dassified as a product sensitising by inhalation (based on available data, the dassification criteria are not met).	GHS/CLP 34.33.
Skin sensitisation: Not dassified	-	-	# Not dassified as a product sensitising by skin contact (based on available data, the dassification criteria are not met).	GHS/CLP 34.33.

GHS/CLP 32.33: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3. Classification of the mixture when data are available for all components or only for some components.

ASPIRATION HAZARD:

Danger dass	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Aspiration hazard: Not dassified	-	-	# Not dassified as a product hazardous by aspiration (based on available data, the dassification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.





Revision: 22/05/2020

SPECIFIC TARGET ORGANS TOXCITY(STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Cutaneous:	RE	Skin	-	# DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/OLP 124.
Neurological:	SE	CNS	Cat.3	# NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/OLP 38.3.4.

GHS/CLP3.8.34: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

Cardnogenic effects: # It is not considered as a carcinogenic product.

Genotoxiaty: # It is not considered as a mutagenic product.

Toxicity for reproduction: # Does not harm fertility. Does not harm the unborn child.

Effects via lactation: # Not dassified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELLAS CHRONIC EFFECTS FROM SHORTAND LONG-TERM EXPOSURE:

Routes of exposure: # May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: # Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system initation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause initation and reversible damage. If swallowed, may cause imitation of the throat and other effects may be the same as described in the exposure to vapours. Long-term or repeated exposure: # Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTME EFFECTS:

Not available.

INFORMATION ABOUT TO XICO CINETICS, METABOLISM AND DISTRIBUTION:

This preparation contains the following substances for which dermal absorption can be very high: Dioctyltin dilaurate.

Basic toxicokinetics: # Not available.

ADDITIONAL INFORMATION:

Not available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological dassification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).

12.1 TOXICITY:

Acute toxicity in aquatic environment	LC50 (OECD 203)	EC50 (OECD 202)	EC50 (OECD 201)
for individual ingredients:	mg/l-96hours	mg/l·48hours	mg/l·72hours
Naphtha (petroleum), hydrotreated heavy	> 8.2 Fishes	> 4.5 Daphnia	> 3.1 Algae

No observed effect concentration

Not available

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATICTOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
Acute aquatic toxicity: Not classified	-	# Not dassified as a hazardous product with acute toxicity to aquatic life (based on available data, the dassification criteria are not met).	GHS/CLP 4.1.3.55.3.
Chronic aquatic toxicity.	Cat.2	# TOXIC: Toxic to aquatic life with long lasting effects.	GHS/OLP 4.1.3.5.5.4.

QLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

Aerobic biodegradation	DQO	%DBO/DQO	<u>Biodegradability</u>
for individual ingredients:	mgO2/g	5days 14 days 28 days	
Naphtha (petroleum), hydrotreated heavy		77.	Easy
Dioctyltin dilaurate		25.	Not easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

NEUCE RH10 WATER Code: 22.08	# III downarios With Negalation (EO) No. 130		OH (20) 110. 1301/20
		, , , , , , , , , , , , , , , , , , ,	RH10 WATERI Code: 22.08

PROOFER



Revision: 22/05/2020

BIOACCUMULATIVE POTENTIAL: 12.3 # Not available.

> BCF Potential Bioaccumulation log Pow > 100. for individual ingredients: Naphtha (petroleum), hydrotreated heavy 5.65 (calculated) Not available Dioctyltin dilaurate 9.26 (calculated) Not available

12.4 MOBILITY IN SOL:

Not available.

Constant of Henry Mobility log Koc **Potential** for individual ingredients: Pa·m3/md 20°C Naphtha (petroleum), hydrotreated heavy 4.91 Not available Dioctyltin dilaurate 8.52 Not available

RESULTS OF PBT AND VPVB ASSESMENT: Annex XIII of Regulation (EC) no. 1907/2006: 12.5

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 OTHERADVERSE EFFECTS:

Ozone depletion potential: # Not available.

Photochemical ozone creation potential: # Not available.

Earth global warming potential: # In case of fire or incineration liberates CO2.

Endocrine disrupting potential: # Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTETREATMENT METHODS: # Directive 2008/98/EC~Regulation (EU) no. 1357/2014: 13.1

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: # Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The dassification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.





Revision: 22/05/2020

SECTION 14: TRANSPORT INFORMATION

14.1 **UN NUMBER:** 1263

14.2 UN PROPER SHIPPING NAME:

TRANSPORTHAZARD CLASS(ES) 14.3

Transport by road (ADR 2019) and Transport by rail (RD 2019):

- Class: - Packing group: Classification code: Tunnel restriction code: (D/E)

3, max ADR 1.1.3.6. 1000 L Transport category: 5 L (see total exemptions ADR 3.4) - Limited quantities: Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4



Packing group: Emergency Sheet (EmS): First Aid Guide (MFAG): F-E,S_E 310,313 - Marine pollutant: Yes. - Transport document: Shipping Bill of lading.

Transport by air (ICAO/IATA2020):

Class: - Packing group:

Air Bill of lading. - Transport document:

Transport by inland waterways (ADN): # Not available.

14.4 PACKING GROUP:

14.5

14.7

See section 14.3

ENMRONMENTAL HAZARDS # Classified as hazardous for the environment.

14.6 SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

TRANSPORT IN BULK ACCORDING TO ANNEX ILOF MARPOL 73/78 AND THE IBC CODE:

Not applicable.

SECTION 15: REGULATORY INFORMATION

EU SAFETY, HEALT HAND ENMRONMENTAL REGULATIONS/LEGISLATION SPECIFIC: 15.1

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

Tactile warning of danger: Not applicable (the classification criteria are not met).

Child safety protection: Not applicable (the dassification criteria are not met).

VOC information on the label

Contains VOC max. 726. g/l - The limit value 2004/42/CE-IA cat. h) for the product ready for use is VOC max. 750. g/l (2010).

OTHER REGULATIONS:

Responsabilidade ambiental:

Autilização deste produto em Portugal fica suje ta ao regime de responsabildade ambiental previsto no DL.147/2008.

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETYASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.



Code: 22 08



Revision: 22/05/2020

SECTION 16: OTHER INFORMATION

TEXT OF THE PHRASE SAND NOTES REFERENCED IN SECTIONS 2 AND/O R3:

Hazard statements according the Regulation (EU) No. 1272/2008~2018/1480 (CLP), Ame x II

H226 Flammable liquid and vapour. H304 May be fatal if swal lowed and enters airways. H315 Causes skin irritation. H336 May cause drowsinessor dizziness. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H3710 May cause damage to organs if swallowed.

Notes related to the identification, classification and labeling of the substances:

Note H: The classification and label shown for this substance applies to the dangerous property(ies) indicated by the risk phrase(s) in combination with the category(ies) of danger shown.

Note P: The dassification as a cardinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1% w/w benzene (ECNo. 200-753-7).

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- # European Chemicals Agency: ECHA, http://echa.europa.eu/
- # · Access to European Union Law, http://eur-lex.europa.eu/
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2017).
- · European agreement on the international carriage of dangerous goods by road, (ADR 2019).
- International Maritime Dangerous Goods Code IMDG induding Amendment 39-1 8 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- # · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- # · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- # · CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- # · EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- # · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- # · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- · SVHC: Substances of Very High Concern.
- # · PBT: Pe is it ent, bio accumulable and toxic substances
- # · vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- # · DNEL: Derived No-Effect Level (REACH).
- # PNEC: Predicted No-Effect Concentration (REACH).
- # · LD50: Lethal dose, 50 percent.
- # · LC50: Lethal concentration, 50 percent.
- # UN: United Nations Organisation.
- * ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- # · MDG: htemational Maritime code for Dangerous Goods.
- # · ATA: International Air Transport Association.
- # ICAO: International Civil Aviation Organization.

SAFETY DATASHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Amex of Regulation (EU) No. 2015/830.

 HISTORIC:
 Revision:

 Vé sion:
 9
 03/02/2015

 Vé sion:
 10
 22/05/2020

Changes since previous Safety Data Sheet:

Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a quarantee of the product's properties.