

A5 – AQUANEUCE – WHITE WATER BASED ACRYLIC PRIMER (ANTI-STAIN)

DESCRIPTION:



This product is based on an acrylic emulsion especially prepared for walls insulation in interior or exterior, when a combined action is pretended, to insulate and to give a certain whiteness to the wall.

FEATURES:

- Good penetration on plaster
- Good resistance to alkalis
- Good power binder of powdery plasters.
- Good applicability
- Good covering power

SPECIFICATIONS:

- **Density** 1,390 ± 0,10
- **Viscosity**..... 65-89 ku (25°C)
- **Color**.....White
- **Superficial drying**..... 4 to 6 hours
- **Depth drying**.....± 24 hours
- **Tenor in CIT/MIT**.....<15 ppm
- **VOC (volatile organic composites)** ^{a)} EU limit value for this product cat. (A/g) 30 g/l (2010). This product contains 8 g/l VOC maximum.

RECOMMENDED USE:

This is used as an insulation coat in the painting of sand-finish, and even stucco walls, before the application of the finish acrylic paint. This also allows to simultaneously insulate and give a certain whiteness to the wall, it is very used in the insulation of stucco interior walls.

SURFACE PREPARATION:

The surface has to be dry, clean, hard and free of bad-adhered particles or dirt. A good brushing is usually enough as preparation.

APPLICATION:

Before to use mix energetically the product.
The application is made with a roller or a paint-brush in a single coat (well-uniformed) without any dilution.

In the case of “poorly porous” walls it is advised a light dilution with water to guarantee a better penetration.

DILUTION: The “AQUANEUCE – WHITE WATER BASED PRIMER” is supplied ready to use. If necessary a dilution with water is possible.

COVERAGE: Variable according to the support’s absorption.
On average and per coat 10 to 12 m² / liter.

CLEAN-UP: With water right after the application.

ADVANTAGES:

- In stucco walls of normal absorption, it doesn’t “glaze.”
- It allows a larger income of acrylic paints applied as finishing.
- As it insulates and simultaneously leaves the wall “half-white”, it allows a better efficiency in the achievement of the final finish.

WARNING: A selection of this product components has a tenor in clorometilisotiazolinona/metilisotiazolinona 3:1 inferior to 15 ppm, according to the Community Directive n°98/8/EC indications. Hence this product is not irritant nor presents any risks of sensitization in a contact with skin.

In spite of presenting no risks for health, it is advised to keep out of reach of children.

STORAGE AND PACKAGING: Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.