

B2 – BELNEUCE – Interior/Exterior Acrylic Paint

DESCRIPTION:



Based on an acrylic dispersion, this paint is very versatile and has finish qualities that makes it the obvious choice for interior and exterior painting, on various types of surfaces, flat or sand-finish plaster, etc. Contains a fungicide and an algacide protection and a good resistance to alkalinity.

FEATURES:

- Easy to apply and with good adhesion.
- Good coverage.
- Good covering power.
- Resistant to cleaning and wet rubbing

SPECIFICATIONS:

- **Density**.....1,500 ± 0,10 (white)
 - **Viscosity**.....85-115 Ku (25°C)
 - **Color**.....White and other soft colors according to the catalog
 - **Finishing**.....Matte
 - **% Solids in volume**.....34 ± 5%
 - **Dry-to-touch**.....± 1 hour
 - **Depth drying**.....± 24 hours
 - **Flashpoint**..... non-flammable
 - **Content in CIT/MIT**.....< 15 ppm.
- VOC (volatile organic compound)**...^{a)} EU limit value set for this product cat. (A/a) 30 g/l (2010). This product contains a maximum of 26 g/l VOC.
- **Reaction to fire classification:** B-s1,d0, according to the norm NP EN 13501-1:2007+A1:2009

RECOMMENDED USE:

To be used for painting and repainting of interior and exterior walls, on various types of plaster, allowing a matte finishing in a wide range of soft colors.

SURFACE PREPARATION:

The new plaster has to be clean, dry, hard, free of any dirt, dust and alkaline efflorescence or “mosses”, before the start of the application.

Concerning repainting, a good brushing of the wall is advised so as to remove old paint remains or to exfoliate. As for exterior walls, the process is facilitated by using a pressurized water-jet cleaning gun.

**SURFACE
INSULATION:**

A careful choice of the 1st coat (insulation) helps to obtain a better finish and to solve certain existing problems in the painting surface.

We recommend as special insulations:

- One coat of “PLIONEUCE PRIMER” – No dilution.
- One coat of “HYDRONEUCE PRIMER” – No dilution.
- One coat of “AQUANEUCE – White Water Based Acrylic Primer” – No dilution.
- One coat of “MARSOL – High Filling Acrylic Primer” – Diluted at 10% with water.
- One coat of “MULTINEUCE – Water Based Acrylic Multi-Use Primer” – No dilution.

APPLICATION:

Before to use mix energetically the product.

The application is made with a paint-brush, a roller or a spray-gun in 2 to 3 coats properly diluted and in a period of 12 to 24 hours.

DILUTION:

With water in the approximate following proportions:

1st Coat.....10%
Others.....5% to 10%

COVERAGE:

Variable according to the support’s absorption, and the application conditions.

On average and per coat 10 to 14 m² / liter.

CLEAN-UP:

With water right after the application.

WARNING:

This product is not irritant nor presents any risks of sensitization in a contact with skin. In spite of presenting no risks for health, it is advised to keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential.

RECOMMENDATIONS:

Do not use in rainy or cold weather.

**STORAGE
AND
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt and 15 liters

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.