

## J1 – ANTI-FUNGUS SOLUTION

### DESCRIPTION:



This product is a combination of conservation agents and fungicides in a water based solution. It allows to eliminate, or at least, to delay fungus (mould) development in walls.

### FEATURES:

- Easy to apply
- Eliminates or delays fungus development

### SPECIFICATIONS:

- **Density**..... 1,017 ± 0,10
- **Viscosity**..... 95 ± 14” Ford IV (20°C)
- **Aspect**..... Whitish liquid

### RECOMMENDED USE:

This product has two types of application:

It is applied directly on the wall over the infested areas with fungus (disinfectant action). In this case, “ANTI-FUNGUS SOLUTION” has to be diluted with water, in equal parts, before the application.

It is applied mixed with the paint as reinforcement and protection against the fungus action. In this case we advise to join to each 15 liters of acrylic paint 2 x ¼ liters of “ANTI-FUNGUS SOLUTION”.

The ranges of acrylic paint that we advise for this action are: “SUVENIL”, “SUPERNEUCE” and “NEUCEBEL”.

The combination of the two applications is more efficient.

### SURFACE PREPARATION:

The areas of the infested wall with fungus (mould) have to be properly washed (in order to remove the fungus) before the application of the “ANTI-FUNGUS SOLUTION”.

Concerning repainting’s, besides the infested areas washing operation, a proper brushing of the wall has to be made in order to eliminate badly adhered paint.

**APPLICATION:** It is applied with a paint-brush or a roller. We advise the following schemes:

New walls:

- 1°. To properly wash the wall
- 2°. To apply directly on the wall the “ANTI-FUNGUS SOLUTION” (diluted in equal parts with water) in order to be well penetrated and let dry for 12 hours.
- 3°. To apply 2 to 3 coats of “acrylic paint” in the chosen color, properly reinforced. **“In every 15 liters of paint to join 2 x ¼ of ANTI-FUNGUS SOLUTION”.**

Repainting:

In this case, after a proper washing of the wall, to apply 2 to 3 coats of acrylic paint in the chosen color reinforced with the “ANTI-FUNGUS SOLUTION” (see “recommend use”).

**DILUTION:** This product is supplied ready to use.

**COVERAGE:** Variable according to the surface absorption. As an orientation: 10 m<sup>2</sup>/liter of mixture (when applied directly to the wall).

**CLEAN-UP:** With water and soap.

**WARNING:**

- Given the toxic nature of the product, we advise a maximum care with its use.
- In case of a contact with the skin or the eyes to wash with plenty of water.
- To keep out of reach of children.

**STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1/4, and 15 liters.