

J3 – DISINFECTANT SOLUTION

DESCRIPTION:



This product is a combination of biocides exempt of CIT/MIT and formaldehyde, with a disinfectant power in a large algacide and fungicide spectrum, in a water based solution. Permits to clean facades, walls and even contaminated ceilings with fungus (mould) and algae, and to prevent their appearance.

FEATURES:

- Easy to use and penetration in plasters.
- Disinfest efficiently contaminated surfaces.

SPECIFICATIONS:

- **Density**.....1,000 ± 0,10
- **Aspect**.....Transparent.

RECOMMENDED USE:

To be applied directly on the infested substrates, to proceed to their cleaning / disinfection, removing algae, mosses, fungi, etc.

APPLICATION:

Applied with a paint-brush or a whitewash brush, abundantly, on the wall.

1°. To wash the wall with a pressurized water-jet cleaning gun, if necessary, to apply a solution of sodium hypochlorite at 5% (bleach) and to wash again the whole surface in order to remove all the hypochlorite.

2°. To apply 1 coat, thick, of “DISINFECTANT SOLUTION”.

3°. To let act 24 to 48 hours.

4°. To brush the whole surface or to wash with a pressurized water-jet cleaning gun. Let dry.

DILUTION:

This product is supplied ready to use.

COVERAGE:

Very variable according to the plaster absorption. As an orientation: 10 m²/liter.

CLEAN-UP:

With water and soap.

WARNING:

To keep out of reach of children.

For further information, the reading of our product **Safety Data Sheet** is essential.

**STORAGE
AND
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1, 5 and 15 liters.