

P1 – ALUNEUCE AG 100 Silver Aluminium General Use

DESCRIPTION: Product formulated with an oil-resinous vehicle and containing aluminium pigments with good fluctuation power (“leafing”). The aluminium particles (with a lamellar form), provide good protection properties.

FEATURES:

- Easy to apply and good lacquering.
- Good covering power.
- Glossy film.

SPECIFICATIONS:

- **Density**.....0,965 ± 0,05
- **Viscosity**.....25 ± 4” Ford IV (20°C)
- **Color**.....Grey, aluminium-like.
- **Gloss**.....Glossy.
- **Superficial drying**.....± 4 hours.
- **Depth drying**.....± 24 hours.
- **VOC (volatile organic compound)**....^{a)} EU limit value set for this product cat. (A/i) 500 g/l (2010). This product contains a maximum of 489 g/l VOC.

RECOMMENDED USE: This product is appropriated for the protection and finish of ferrous structures, whether in the interior or in the exterior, when a finish with the characteristic aspect of the aluminium is pretended. It can be applied directly on the iron (properly cleaned and free of rust), or, for a better protection, over “anticorrosive primers”, such as “NEUCEPRIMER OXI”, “NEUCERAPID PRIMER”. It is very used in the protection and finish of “metallic frameworks”.

SURFACE PREPARATION: Very often, the pellicular defects of the paints are the consequence of a deficient surface preparation. Therefore, before the application of “ALUNEUCE AG 100”, to make sure that the ferrous surface is dry, clean, free of rust or dirt, and properly degreased.

APPLICATION: To homogenize well the product before to use. It is applied with a paint-brush (preferentially), in a single coat, but in a sufficient layer that ensures a dry film thickness of ±25 µm.

- DILUTION:** With “SYNTHETIC DILUENT”, if necessary up to 5%.
- COVERAGE:** On average and per coat: 8 to 10 m²/liter.
- CLEAN-UP:** With “SYNTHETIC DILUENT”, or "CELLULOSE DILUENT", right after the application.
- WARNING:**
- Inflammable product.
 - In the case of a contact with the skin or the eyes, to wash with plenty of water.
 - Toxic by inhalation or ingestion.
 - For further information, please read our product **Safety Data Sheet**.
- RECOMMENDATIONS:** Do not apply with temperatures inferior to 5°C or with a rainy weather.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 1 year after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of ¼ lt, 1lt and 5 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.