

W3 – NEUCEDECK – Protector Oil for decks

DESCRIPTION:



Perfect for any wood surface exposed to the weather, **NEUCEDECK**, is an oil with a high depth penetration, water repellent and passable, formulated with water emulsified copolymers based on linseed oil, which enhances and protects the natural beauty of the wood.

Low odor, **NEUCEDECK**, protects against the action of intense atmospheric agents, against the UV rays action, fungi and algae, and prevents warping and cracking caused by the wood excessive dryness.

Easy application with a matte finish, doesn't create a film, so it does not break or peel, it is easy to be maintained and restored, is a versatile solution for all situations in which an excellent protection is needed.

FEATURES:

- Easy to apply.
- Deeply penetrates in the wood.
- Good water repellency.
- Does not create a film.
- Easy maintenance.
- Good preventive properties against fungi of wood.
- Resistance to U.V.
- Passable.

SPECIFICATIONS:

- **Density**..... 0.996 ± 0.05
- **Viscosity**..... 15 ± 2" Ford IV (20°C)
- **Aspect** Milky
- **Finishing**..... Incolor mate
- **Dry-to-touch**..... 30 min
- **Drying between coats** 2 hours
- **Drying to be passable**..... 24 hours
- **VOC (volatile organic compound)**...^{a)} EU limit value set for this product cat. (A/f) 130 g/l (2010). This product contains a maximum of 7.0 g/l VOC.

RECOMMENDED

USE:

Thanks to its qualities, "NEUCEDECK" is specially recommended for the protection and maintenance of wood decks. It is recommended for both new wood and previously varnished or painted wood, in many different situations as doors, windows, garden furniture, etc...

SURFACE

PREPARATION:

Generally speaking, the wood has to be dry, clean and free of dust, grease and other contaminants.

To properly sand with medium grain sandpaper and this sanding

operation must be done in the fibers direction.
Remove all traces of wax on woods previously waxed.

Concerning a wood with varnish or degraded paint, to make sure its complete removal, carefully scraping the wood, then proceed to its sanding and cleaning in order to ensure the proper oil penetration.

APPLICATION:

To mix the product until its total homogenization before to apply.
To apply **NEUCEDECK** with a paint-brush in the direction of the wood grain until it's saturated, the number of the needed coats depending on the type of wood and its percentage of humidity. Normally 2 to 3 coats are applied.
At the end of 30-45 minutes after the last application, to remove any excess of oil with a dry and soft cloth.
To let the floor deck to dry for at least 24 hours before being passable.
To proceed to an annual maintenance, applying 1 to 2 coats of **NEUCEDECK** on the surface properly cleaned.

DILUTION:

NEUCEDECK is supplied ready to apply.
However, it can be diluted, between 5-10%, with water in case of woods with very low porosity

COVERAGE:

On average and per coat: 10 to 12 m² / liter, depending on the wood porosity and the application conditions.

CLEAN-UP:

With water right after the application.

WARNING:

- To keep out of reach of children.
- Do not throw any residue in the drains.
- For further information, the reading of our product **Safety Data Sheet** is essential

RECOMMENDATIONS:

To apply the product with temperatures superior to 5°C or a surface humidity inferior to 15%.
Do not apply this product if there is a probability of rain in the next 24 hours.
The time period for the maintenance of wood may be affected by the type of wood and the type of exposure to which it will be subjected to.

**STORAGE
AND
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 1 year after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 0.75 and 4 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.