

## W6 – NEUCEDESCOF Solvent Removal Oil (De-molding)

- DESCRIPTION:** This product is based on a combination of oily products. Aims at facilitate the de-molding operation of the fair-faced concrete structures (raw concrete).
- FEATURES:**
- Slow drying.
  - Difficults the adhesion between concrete and the wood or metal mold.
- SPECIFICATIONS:**
- **Density**.....0,900 ± 0,05
  - **Viscosity**.....25 ± 4” Ford IV (20°C)
  - **Color**.....Yellowish
  - **Aspect**.....Oily
  - **Drying**.....Difficult, always leaving an oily residue on the mold
- RECOMMENDED USE:** It is applied in the interior side of the wood or metal molds which are used as “formwork” in fair-faced concrete structures.
- SURFACE PREPARATION** The mold surface doesn’t need any preparation. However the cleaner it is, the bigger is the product success.
- APPLICATION:** To mix well the product before to apply.  
The application is made with a paint-brush in a thick coat, in order to guarantee that the wood or metal surface remains perfectly oily, fact that will facilitate the de-molding operation.
- DILUTION:** This product is supplied ready to use.
- COVERAGE:** Variable according to the mold absorption. As an orientation: 7 to 9 m<sup>2</sup>/liter.
- CLEAN-UP:** With “SYNTHETIC DILUENT”.
- WARNING:** In the case of a contact with the skin or the eyes, to wash with plenty of water.
- STORAGE AND PACKAGING:** The packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 5lt and 20 liters.