

Code: 50225000



Version: 3 Revision: 21/10/2019 Previous revision: 08/06/2017 Date of printing: 21/10/2019

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER: **ENDURECEDOR NEUCEROCK** 

Code: 50225000

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended uses (main technical functions): [X] Industrial [X] Professional # Hardener, in combination with hydroxylated polymers, mainly polyesters and polyacrylates, in order to prepare 2 component systems.

Sectors of use:

Industrial manufacturing (SU3).

Professional uses (SU22).

Uses advised against:

# This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as

'Intended or identified uses'. For professional use only.

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

# Restricted to professional users. Contains CMR substances, categories 1A or 1B: Restricted to professional users. Forbidden to the general public. The restrictions do not apply to storage, keeping, treatment, filling into containers, or transfer from one container to another of the substances for export. See entry 28 and/or 29 and/or 30 in the Annex of the Regulation (EC) No.  $552/2009 \sim 276/2010$ .

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

NEUCE - Indústria de Tintas, S.A.

Rua Francisco Rocha - Aptdo. 4514 - 3700-892 - Romariz SJM (Portugal)

Phone: +351 256 840040 - Fax: +351 256 840049

E-mail address of the person responsible for the Safety Data Sheet:

e-mail: geral@neuce.pt

1.4 EMERGENCY TELEPHONE NUMBER: +351 256 840041 (9:00-18:30 h.) (working hours)

### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

## ication in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP):

DANGER: Flam. Liq. 3:H226 | Skin Irrit. 2:H315 | Eye Irrit. 2:H319 | Muta. 1B:H340 | Carc. 1B:H350 | Aquatic Chronic 3:H412 | EUH066

Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Physicochemical:	Flam. Liq. 3:H226 c) Skin Irrit. 2:H315 c) Eye Irrit. 2:H319 c) Muta. 1B:H340 c) Carc. 1B:H350 c) Aquatic Chronic 3:H412 c)	Cat.3 Cat.2 Cat.2 Cat.1B Cat.1B Cat.3	Skin Eyes	Skin Eyes	- Irritation Irritation Genetic defects Cancer
<b>\$</b> 1	EUH066 c)	-	Skin	Skin	Dryness, Cracking
Environment:					

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

#### 2.2 LABEL ELEMENTS:



This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP)

lazard statements:

H226 Flammable liquid and vapour. H350 May cause cancer.

H340 May cause genetic defects. H319 Causes serious eye irritation. H315 Causes skin irritation.

Harmful to aquatic life with long lasting effects. H412

<u>Precautionary statements:</u> P102 Keep out of reach of children.

P201-P202-P405 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Store locked up.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





Autoclassified

< ATP01

Index No. 648-010-00-X

P280F Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash with P303+P361+P353-P352-P312

plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact I ensies, if pies ent and easy to do. P305+P351+P338

P273-P501a Avoid release to the environment. Dispose of contents/container in accordance with local regulations.

Supplementary statements:

EUC028 Restricted to professional users.

Continue rinsing.

Substances that contribute to classification: Aromatic hydrocarbons C8 (redistillate)

2.3 OTHER HAZARDS

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: Other physicochemical hazards: Vapours may form with air a mixture potentially flammable or explosive. Other adverse human health effects: Prolonged exposure to vapours may produce transient drows iness. Other negative environmental effects: Does not contain substances that fulfil the PBT/vPvB criteria.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

3.1 SUBSTANCES

Not applicable (mixture).

3.2 **MIXTURES** 

This product is a mixture.

Chemical description:

Solution of polyamide resin in organic solvents.

**INGREDIENTS:** 

60 < 70 % Fatty acids, C18-unsatd

CAS: 198028-08-9, EC: Polymer  $\langle \rangle$ 

REACH: Exempt (polymer)

CLP: Warning: Skin Irrit. 2:H315 | Eye Irrit. 2:H319 | Aquatic Chronic 3:H412

40 < 50 % **⟨७**⟨**\$**⟩⟨!⟩

Aromatic hydrocarbons C8 (redistillate)

CAS: 90989-38-1, EC: 292-694-9

CLP: Danger: Flam. Lig. 3:H226 | Acute Tox. (inh.) 4:H332 | Acute Tox (skin) 4:H312 |

Skin Irrit. 2:H315 | Muta. 1B:H340 | Carc. 1B:H350 | Asp. Tox. 1:H304

# Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None

Reference to other sections

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 15/01/2019.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.

Revision: 21/10/2019



ENDURECEDOR NEUCEROCK

Code: 50225000



### **SECTION 4: FIRST AID MEASURES**

#### 4.1 **DESCRIPTION OF FIRST-AID MEASURES:**



# In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u>	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin:	Skin contact causes redness. Prolonged contact may cause skin dryness.	# Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
Eyes:	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
<u>Inqestion:</u>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	# If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: 4.3 Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient. Antidotes and contraindications: Specific antidote not known.

## **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1 EXTINGUISHING MEDIA

Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

#### SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: 5.2

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, nitrogen oxides, ammonia. Exposure to combustion or decomposition products may be a hazard to health.

#### 5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the winddirection.

#### 6.2 ENVIRONMENTAL PRECAUTIONS

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

#### 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

# Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.

#### 6.4 REFERENCE TO OTHER SECTIONS:

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.

Code: 50225000



### **SECTION 7: HANDLING AND STORAGE**

7.1 PRECAUTIONS FOR SAFE HANDLING:

Comply with the existing legislation on health and safety at work.

Avoid any type of leakage or escape. Keep the container tightly closed.

Recommendations for the prevention of fire and explosion r

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.

Flash point

Autoignition temperature

- Upper/lower flammability or explosive limits Recommendations for the prevention of toxicological risks:

464\* oC. 1.1\* - 7.0 % Volume 25°C

# Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

Recommendations for the prevention of environmental contamination:

Avoid any spillage in the environment. Pay special attention to the clearing water. In the case of accidental spillage, follow the instructions indicated in section 6.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.

According to current legislation. Class of storage

Maximum storage period 12. months

Temperature interval min: 5. °C, max: 35. °C (recommended).

Incompatible materials:

Keep away from oxidixing agents, from strongly alkaline and strongly acid materials.

According to current legislation.

Limit quantity (Seveso III): Directive 2012/18/EU:
- Named dangerous substances/mixtures: None

- Hazard categories and lower-/upperthreshold quantities in tonnes (t):
- · Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t).
- · Health hazards: Not applicable
- · Environmental hazards: Not applicable
- Other hazards: Not applicable.
- Threshold quantity for the application of lower-tier requirements: 5000 tons
- Threshold quantity for the application of upper-tier requirements: 50000 tons

The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.

#### 7.3 SPECIFIC END USES:

# For the use of this product do not exist particular recommendations apart from that already indicated.



Code: 50225000



# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

### OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2018	<u>Year</u>	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Xylene	1996	100.	434.	150.	651.	A4

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A4 - Non classified as carcinogenic in humans.

It is applicable the Directive 90/394/EEC~1999/38/EC, on the protection of the health and safety of workers from the risks related to carcinogenic or mutagenic agents at work.

## BIOLOGICAL LIMIT VALUES:

Not available

### DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recomme reded by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers: - Systemic effects, acute and chronic: Fatty acids, C18-unsatd	DNEL Inhalation mg/m3 - (a)	- (c)	DNEL Cutaneous mg/kg bw/d - (a)	- (c)	DNEL Oral mg/kg bw/d - (a)	- (c)
Derived no-effect level, workers: - Local effects, acute and chronic: Fatty acids, C18-unsatd	DNEL Inhalation mg/m3 - (a)	- (c)	DNEL Cutaneous mg/cm2 - (a)	- (c)	DNEL Eyes mg/cm2 - (a)	- (c)

# Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(-) - DNEL not available (without data of registration REACH).



Code: 50225000



Page 6/12

Revision: 21/10/2019

# PREDICTED NO-EFFECT CONCENTRATION (PNEC):

Predicted no-effect concentration, aquatic organisms: - Fresh water, marine water and intermittent release: Fatty acids, C18-unsatd	PNEC Fresh water mg/l -	PNEC Marine mg/I	PNEC Intermittent mg/l -
- Wastewater treatment plants (STP) and sediments in fresh- and marine water: Fatty acids, C18-unsatd	PNEC STP mg/l	PNEC Sediments mg/kg dw/d -	PNEC Sediments mg/kg dw/d
Predicted no-effect concentration, terrestrial organisms: - Air, soil and effects for predators and humans: Fatty acids, C18-unsatd	PNEC Air mg/m3	PNEC Soil mg/kg dw/d	PNEC Oral mg/kg dw/d

(-) - PNEC not available (without data of registration REACH).

### 8.2 EXPOSURE CONTROLS:

### **ENGINEERING MEASURES:**











Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

<u>Protection of respiratory system:</u> Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

### OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Thanaractar cr 5 of 11 Er	
Mask:	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety qoqqles:	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.
Gloves:	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min.When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min.The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

# Advisable. Put away work clothes under control and separately from the rest. Do not take contaminated clothing home. Wash contaminated work clothes before wearing them again.

### Thermal hazards:

Clothing:

Not applicable (the product is handled at room temperature).

# Advisable.

# ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

<u>Spills in water:</u> Do not allow to escape into drains, sewers or water courses.

- Water Management Act: This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.



Code: 50225000



Revision: 21/10/2019

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the

atmosphere.

- VOC (product ready for use\*): It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Amex I.1): Emission subcategory j) Two-pack performance coating, solvent-borne. (VOC max. 500. g/l\* starting from 01.01.2010).

- VOC (industrial installations): # If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 40.0% Weight, VOC (supply): 40.0% Weight, VOC: 36.2% C (expressed as carbon), Molecular weight (average): 106.2, Number C atoms (average): 8.0, VOC CMR Cat.1+2: 40.0%.

	(average): 8.0, VOC CMR Cat.1+2: 40.0%.	iborij	, i-iorcculai	weight (ave	rage). 100.2 , Number e al	Coms
SECTIO	ON 9: PHYSICAL AND CHEMICAL PROPERTIES					
9.1	INFORMATIONON BASIC PHYSICAL AND CHEMICAL PROPERTIES: Appearance					
	- Physical state - Colour	:	Liquid. # Colourle	ess.		
	- Odour - Odour threshold	:	Character		a)	
	<u>pH-value</u>			ibie (ITiixtui e	c).	
	- pH Change of state	•	Alkaline			
	- Melting point - Initial boiling point	:	Not applic	able (mixtu 137.2*	re). °C at 760 mmHg	
	Density - Vapour density	:	#	<i>3.6</i> 6*		Relative air
	- Relative density Stability	:	#	0.95	# at 20/4°C	Relative water
	- Decomposition temperature Viscosity:	:	Not availa	ble (technic	al impossibility to obtain t	he data).
	- Kinematic viscosity Volatility:	:	# Not app	licable		
	- Evaporation rate	:	#	78.4*		Relative
	- Vapour pressure - Vapour pressure	:		/* 4.5*	mmHg at 20°C kPa at 50°C	
	Solubility(ies) - Solubility in water	:	Not applic	able		
	- Liposolubility - Partition coefficient: n-octanol/water	:		<i>ilable (mixt</i> able (mixtu	ure untested). re).	
	Flammability: - Flash point		. toe appe	25*	°C	
	- Upper/lower flammability or explosive limits		# 1 #	1* - 7.0	% Volume 25°C	
	- Autoignition temperaturé Explosive properties:		-	464*	°C	
	Vapours can form explosive mixtures with air and are able to flame up or explosing properties:	xplod	e in presenc	e of an igniti	on source.	
	Not classified as oxidizing product.					
	*Estimated values based on the substances composing the mixture.					
9.2	OTHER INFORMATION: - Solids		#	E0 E	# % Volume	
	- VOC (supply)	- :	#		% Weight	
	The values indicated do not always coincide with product specifications. Th technical data sheet. For additional information concerning physical and ch					
	and 12.		p p		,	
SECTIO	DN 10: STABILITY AND REACTIVITY					
10.1	REACTIVITY:					
	Corrosivity to metals: It is not corrosive to metals.  Pyrophorical properties: It is not pyrophoric.					
10.2	CHEMICAL STABILITY:					
	Stable under recommended storage and handling conditions.					
10.3	POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with oxidizing agents, acids.					
10.4	CONDITIONS TO AVOID: Heat: Keep away from sources of heat.					
	Light: If possible, avoid direct contact with sunlight.					
	Air: The product is not affected by exposure to air, but should not be left the Humidity: Avoid extreme humidity conditions.	e CONU	amers open			
	Pressure: Not relevant.  Shock: The product is not sensitive to shocks, but as a recommendation of the product is not sensitive to shocks.					
	avoid dents and breakage of packaging, especially when the product is hand	dled ir	n large quant	ities, and du	uring loading and download	operations.
10.5	INCOMPATIBLE MATERIALS: Keep away from oxidixing agents, from strongly alkaline and strongly acid r	mater	rials.			
10.6	HAZARDOUS DECOMPOSITION PRODUCTS:					
-	# As consequence of thermal decomposition, hazardous products may be p	oroduo	ced: nitroge.	n oxides, am	nmonia.	

Revision: 21/10/2019

ENDURECEDOR NEUCEROCK

Code: 50225000



# **SECTION 11: TOXICOLOGICAL INFORMATION**

No experimental toxicological data on the preparation is available. The toxic dog call dassification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No.  $1272/2008 \sim 2018/1480$  (CLP).

#### 11.1 INFORMATIONON TOXICOLOGICAL EFFECTS:

## **ACUTE TOXICITY:**

Dose and lethal concentrations for individual ingredients: Fatty acids/isophthalic acid/TETA aduct Aromatic hydrocarbons C8 (redistillate)	LD50 (OECD 401) mg/kg bw oral > 2000. Rat 4300. Rat	LD 50 (OECD 402) mg/kg bw cutaneous > 2000. Rabbit 1700. Rabbit	LC50 (OECD 403) mg/m3·4h inhalation > 22080. Rat
Estimates of acute toxicity (ATE) for individual ingredients: Fatty acids/isophthalic acid/TETA aduct Aromatic hydrocarbons C8 (redistillate)	ATE mg/kg bw oral - -	ATE mg/kg bw cutaneous 1700.	MTE mg/m3-4h inhalation 11000.* Vapours

- (\*) Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.
- (-) The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available

owest observed adverse effect level

Not available

INFORMATIONON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

I'W O'W WITON CHEET NOOTED O' BY O'SONE! NICKEE CONCRET!								
Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria				
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/QLP 3.1.3.6.				
Skin: Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.				
Eyes: Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.				
Ingestion: Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.				

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

# CORROSION / IRRITATION / SENSITISATION:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Respirat any corros io ny ir ritation Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
Skin corrosion/irritation:	Skin	Cat.2	IRRITA NT: Causes skin irritation.	GHS/CLP 3.2.3.3.
Serious eye damage/irritation:	Eyes	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
Respirat or y sens it is at ion: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
Skin sensitisation: Not classified	-	-	# Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

Code: 50225000



Page 9/12

Revision: 21/10/2019

**ASPIRATION HAZARD:** 

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET OR GANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects S	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Cutaneous:</u> F	RE	Skin	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.

### CMR EFFECTS:

Carcinogenic effects:

This preparation contains the following ingredients which can cause cancer:

Aromatic hydrocarbons C8 (redistillate) (cat.1B)

Genotoxicity:

This preparation contains the following ingredients which can be mutagenic:

Aromatic hydrocarbons C8 (redistillate) (cat.1B)

Toxicity for reproduction: Does not harm fertility. Does not harm the unborn child.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

### DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: # Harmful by inhalation. Harmful in contact with skin. Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. Irritating to skin. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.

Long-term of repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

# INTERACTIVE EFFECTS:

Not available.

INFORMATI ON A BOUT TO XICOCINETICS, METABOLISM AND DISTRIBUTION:

<u>Dermal absorption:</u> Not available. <u>Basic toxicokinetics:</u> Not available.

ADDITIONAL INFORMATION:

Not available.

# **SECTION 12: ECOLOGICAL INFORMATION**

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).

	_
171	TOXICITY:
12.1	IOAICII.

Acute toxicity in aquatic environment	LC50 (OECD 203)	EC50 (OECD 202)	EC50 (OECD 201)	
for individual ingredients:	mg/l·96hours	mg/l-48hours	mg/l·72hours	
Aromatic hydrocarbons C8 (redistillate)	135. Fishes	> 16. Daphnia	> 2.2 Algae	
		•	•	

No observed effect concentration

Not available

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria			
Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.			
Chronic aquatic toxicity:	Cat.3	HARMFUL: Harmful to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.			

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

SAFETY DATA SHEET (REACH) in accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830					Revision: 21/10/2019 Page 10 / 12			
	IEUCE ITURO DA TINTA	ENDURECEDOR NEUCEROCK Code: 50225000					4	
12.2	PERSISTENCE A Not available.	AND DEGRADABILITY:					-	
			DQC mgC		%DBO/DQO 5 days 14 days		Biodegra Not easy Easy	<u>-</u>
	Note: Biodegradability data correspond to an average of data from various bibliographic sources.							
12.3	BIOACCUMULA # Not available	TIVE POTENTIAL:						
		<u>n</u> gredients : ohthalic acid/TETA aduct carbons C8 (redistillate)	<u>log F</u>	<u>Pow</u> 2.95	BCF L/kg 29.	(calculated)	Potential  Not avail  Not avail	able
12.4	MOBILITY IN Son Not available.	OIL:	'					
		gredients : ohthalic acid/TETA aduct carbons C8 (redistillate)	<u>log H</u>	<u>√oc</u> 1.70	Constant of H Pa·m3/mol 200 660.		Potential  Not avail  Not avail	able
12.5		IT AND VPVB ASSESMENT: Annex XIII of Regin substances that fulfil the PBT/vPvB criteria.	ulation (EC) no. 1907/	2006:				
12.6	Photochemical Earth global wa Endocrine disru	n potential: Not available. ozone creation potential: Not available. rming potential: In case of fire or incineration libe oting potential: Not available.	erates CO2.					
SECTIO	N 13: DISPOS	SAL CONSIDERATIONS						

# 13.1

WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014:
Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Wast e should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

<u>Disposal of empty containers:</u> Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU: Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

<u>Procedures for neutralising or destroying the product:</u>
Controlled incineration in special facilities for chemical waste, in accordance with local regulations.



Code: 50225000



### **SECTION 14: TRANSPORT INFORMATION**

14.1 UN NUMBER: 1263

14.2 UN PROPER SHIPPING NAME:

PAINT

TRANSPORT HAZARD CLASS(ES): 14.3

<u>Transport by road (ADR 2019) and Transport by rail (RID 2019):</u>

- Class: 3 Packing group:Classification code: III F1 Tunnel restriction code: (D/E)

Transport category: 3, max. ADR 1.1.3.6. 1000 L - Limited quantities: 5 L (see total exemptions ADR 3.4)

- Transport document: Consignment paper. ADR 5.4.3.4 - Instructions in writing:

Transport by sea (IMDG 38-16):

Class: - Packing group: IIIEmergency Sheet (EmS):First Aid Guide (MFAG): F-E,S\_E 310,313 - Marine pollutant: No.

Shipping Bill of lading. - Transport document:

Transport by air (ICAO/IATA 2018):

- Class: - Packing group: III

Air Bill of lading. - Transport document:

Transport by inland waterways (ADN): Not available.

14.4 PACKING GROUP:

14.7

See section 14.3

**ENVIRONMENTAL HAZARDS:** 14.5 # Not applicable.

14.6 SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

TRANSPORT IN BULK ACCORDING TO ANNEX LIOF MARPOL 73/78 AND THE IBC CODE Not applicable.

### **SECTION 15: REGULATORY INFORMATION**

15.1 EU SAFETY, HEALT HAND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use: See section 1.2

<u>Tactile warning of danger:</u> Not applicable (the classification criteria are not met).

Child safety protection: Not applicable (the classification criteria are not met).

VOC information on the label: Contains VOC max. 300. g/l - The limit value 2004/42/CE-IIA cat. j) for the product ready for use is VOC max. 500. g/l (2010).

OTHER REGULATIONS:

Responsabilidade ambiental:

A utilização deste produto em Portugal fica sujeita ao regime de responsabilidade ambiental previsto no DL.147/2008.

Control of the risks inherent in major accidents (Seveso III): See section 7.2

Other local legislations:

# The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.









Code: 50225000



Page 12 / 12

Revision: 21/10/2019

### **SECTION 16: OTHER INFORMATION**

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3: Hazard statements according the Regulation (EU) No. 1272/2008~2018/1480 (CLP), Annex III

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H412 Harmful to aquatic life with long lasting effects. H340 May cause genetic defects. H350 May cause cancer.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

# ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

# MAIN LITERATURE REFERENCES AND SOURCES FOR DATA

- · European Chemicals Agency: ECHA, http://echa.europa.eu/
- · Access to European Union Law, http://eur-lex.europa.eu/ · Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2017).
   European agreement on the international carriage of dangerous goods by road, (ADR 2019).
- International Maritime Dangerous Goods Code IMDG including Amendment 38-16 (IMO, 2016).

### ABBREVIATIONS AND ACRONYMS

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- · ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- · VPVB: Very persistent and very bioaccumulable substances. · VOC: Volatile Organic Compounds.
- · DNEL: Derived No-Effect Level (REACH).
- · PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- · IMDG: International Maritime code for Dangerous Goods.
- · IATA: International Air Transport Association.
- · ICAO: International Civil Aviation Organization.

# FETY DATA SHEET REGULATIONS

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

HISTORIC: 08/06/2017 Version: 2 21/10/2019 Version: 3

# Changes since previous Safety Data Sheet:

# Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.