

U34 – RH20 WATERPROOFER – Solvent-based

DESCRIPTION: Product formulated with acrylic resins of high resistance to UV rays, atmospheric agents, etc, advised for the waterproofing of porous mineral surfaces, providing hydrophobic properties and a glossy finish.

FEATURES:

- Easy to apply and quick drying.
- Great penetration.
- Isolate and protect, strengthening the surface
- Great resistance to the natural ageing of the alkalis.

SPECIFICATIONS:

- **Density**.....0,920 ± 0,05
- **Viscosity**.....25 ± 4” Ford IV (20°C)
- **Colour**.....Colourless
- **Finishing**Glossy
- **Superficial drying**.....± 30 minutes
- **Drying between coats**.....12 to 24 hours
- **Solid content in volume** 25±2%
- **Flashpoint** 46°C
- **VOC (volatile organic compound)**...^{a)} EU limit value set for this product cat. (A/h) 750 g/l (2010). This product contains a maximum of 654 g/l VOC.

**RECOMMENDED
USE:**

Used for the insulation / waterproofing of concrete, shale, granite, masonry, asbestos-cement, clay tile, etc, in general for the porous mineral substrates, both in interior and exterior.

**SURFACE
PREPARATION:**

Surfaces have to be properly cleaned, dried and free of badly adhered material. As this product doesn't cover imperfections, the surface should already be with a final aspect before the application.

APPLICATION:

To apply with a roller, a paint-brush or a spray-gun, in 2 coats without dilution.

DILUTION:

This product is supplied ready to use.

COVERAGE:

Highly variable according to the surface absorption and the application conditions. As an orientation, we can indicate 9 to 12 m²/liter.

CLEAN-UP: With “CELLULOSE DILUENT”, right after the application.

WARNING:

- To apply in places with a good air renewal.
- When applied with a spray-gun, to use a mask and gloves protection.
- Inflammable product.
- In the case of a contact with the skin or the eyes, to wash with plenty of water.
- To keep out of reach of children.
- For further information, please read our product **Safety Data Sheet**.

RECOMENDAÇÕES: Do not apply on hot surfaces because of solar exposition. Temperature of application between 5°C and 35°C, relative humidity inferior to 80%, surface temperature 2 to 3°C above the dew point.

Do not apply on damp surfaces.

**STORAGE
AND
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt and 20 liters

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.