



## W12 – IMUNEUCE Wood Protector

**DESCRIPTION:** Formulated with a mixture of fungicide and insecticide products in

an oily environment, this product is destined to the preservation of

the wood.

**FEATURES:** - Good bactericide and fungicide power.

- Good wet and penetrating power.

- It eliminates the "wood bug".

- **Viscosity**...... 15 ± 2" Ford IV (20°C)

Color Colorless, Brown and green.

Superficial drying.....±12 hours.Depth drying.....±24 hours.

RECOMMENDED USE:

The main function of "IMUNEUCE" is to protect and preserve the

wood against the "wood bug" action.

This function becomes fundamental when the wood is fair-faced, in case of beams and lathes presence in attics, wood for linings, or other similar situations. As it is manufactured in the brown and green color, it gives the possibility to transmit simultaneously to the

wood a decorative effect and protection.

SURFACE

**PREPARATION:** absorption capacity.

**APPLICATION:** To mix well the product before to apply.

The application is made with a paint-brush, in 1 or 2 coats without

The wood surface has to be clean, dry, free of dirt, and with an

dilution, and in order to keep the wood well impregnated.

After 48 hours, and in required situations, a varnishing with

"NEUCELAC" can be effectuate.

**DILUTION:** This product is supplied ready to use.

**COVERAGE:** Depending, more or less, on the wood absorption.

As an orientation: 4 to 5 m<sup>2</sup>/liter.

**CLEAN-UP:** With "SYNTHETIC DILUENT", right after the application.





**WARNING:** 

- Inflammable product.
- In the case of a contact with the skin or the eyes, to wash with plenty of water and soap.
- As we are dealing with a toxic product, to handle it with care.
- Keep out of reach out children.

STORAGE AND PACKAGING: Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt, 20lt and 200 liters.